

DOUBLE COATED POLYESTER TAPE

A 1/2 mil (.0005) thick polyester film coated on both sides with an aggressive, high quick stick, high peel and high shear strength acrylic adhesive system. The adhesive has excellent high temperature resistance and has a built in ultraviolet resistant stabilizer system. Adhesion is excellent to metals, glass, films, craft paper and most coated papers.

Name	Imperial Typical Value	Typical Value (Metric)
Thickness Liner	3.75 mils	0.095 mm
Peel Adhesion Exposed	65 oz/inch width	18.4 N/2.5 cm
Shear Strength Exposed	Indefinite @ 4 psi	Indefinite @ 27.6 kPa
Tensile Strength	7.5 lbs/inch width	34.9 N/2.5 cm
Elongation	100%	100%
Minimum Appl	-20 degrees F	-29 degrees C
Maximum Use Temp	270 degrees F	132 degrees C

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Contact Venture Tape today for a complete list of products or a free sample
 Toll Free North America 800-343-1076
 From United Kingdom 0-800-962-957
 From Australia 1-800-122-797
www.venturetape.com
www.boma.it



USA
 Venture Tape Corp.
 30 Commerce Road
 Rockland, MA 02370
 781-331-5900
 FAX 781-871-0065
www.venturetape.com

Europe - Venture Tape
 Venture Tape Europe Corp.
 Units 5 - 6, Faraday Close,
 Drayton Fields, Daventry,
 Northamptonshire, England NN11 8RD
 (0) 1327 876555
 FAX (0) 1327 876444

Australasia
 Venture Tape Australasia, Pty., Ltd.
 11B Production Drive
 Campbellfield, VIC 3061
 Australia
 (03) 9357 6025
 FAX (03) 9357 6045