

## DOUBLE COATED POLYESTER TAPE TISSUE VERSION

*A thin, conformable, non woven tissue coated on both sides with an extremely aggressive, high tack rubber based adhesive system. The adhesive has excellent balance of peel and shear properties along with good heat resistance. This is a tissue version of VT 512 double coated polyester tape.*

Name	Imperial Typical Value	Typical Value (Metric)
Thickness Carrier	1.3 mils	0.0330 mm
Thickness Adhesive Exposed	3.0 mils	0.0762 mm
Peel Adhesion Exposed	70 oz/inch width	19.8 N/2.5 cm
Shear Strength Exposed	Indefinite @ 2.2 psi	Indefinite @ 15.2 kPa
Tensile Strength	6 lbs/inch width	27.2 N/2.5 cm
Elongation	5%	5%
Minimum Appl	40 degrees F	4 degrees C
Maximum Use Temp	175 degrees F	80 degrees C

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

**Contact Venture Tape today for a complete list of products or a free sample**  
 Toll Free North America 800-343-1076  
 From United Kingdom 0-800-962-957  
 From Australia 1-800-122-797  
[www.venturetape.com](http://www.venturetape.com)  
[www.boma.it](http://www.boma.it)



**USA**  
 Venture Tape Corp.  
 30 Commerce Road  
 Rockland, MA 02370  
 781-331-5900  
 FAX 781-871-0065  
[www.venturetape.com](http://www.venturetape.com)

**Europe - Venture Tape**  
 Venture Tape Europe Corp.  
 Units 5 - 6, Faraday Close,  
 Drayton Fields, Daventry,  
 Northamptonshire, England NN11 8RD  
 (0) 1327 876555  
 FAX (0) 1327 876444

**Australasia**  
 Venture Tape Australasia, Pty., Ltd.  
 11B Production Drive  
 Campbellfield, VIC 3061  
 Australia  
 (03) 9357 6025  
 FAX (03) 9357 6045