

SPLICING TAPE

VentureTape 526 is a blue double coated tissue tape coated on both sides with a versatile acrylic pressure sensitive adhesive (PSA). A conformable effective splicing tape specifically designed for uneven surfaces and demanding bonding applications, VentureTape 526 provides an excellent bond on paper, plastics, and other film materials.

Features & Benefits

- Conformable and versatile splicing tape used

Name	Imperial Typical Value	Typical Value (Metric)
Thickness Carrier	1.3 mils	33.0 mm
Thickness Adhesive Exposed	1.5 mils	38.1 mm
Thickness Adhesive Liner	1.5 mils	38.1 microns
Thickness Liner	3.3 mils	83.8 microns
Peel Adhesion Exposed	48 oz/inch width	13.3 N/25 mm
Peel Adhesion Liner	48 oz/inch width	13.3 N/25 mm
Shear Strength Exposed	>168 hrs	>168 hrs
Shear Strength Liner	>168 hrs	>168 hrs
Minimum Appl	-20 degrees F	-29 degrees C
Maximum Use Temp	220 degrees F	104 degrees C

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Contact Venture Tape today for a complete list of products or a free sample
 Toll Free North America 800-343-1076
 From United Kingdom 0-800-962-957
 From Australia 1-800-122-797
www.venturetape.com
www.boma.it



USA
 Venture Tape Corp.
 30 Commerce Road
 Rockland, MA 02370
 781-331-5900
 FAX 781-871-0065
www.venturetape.com

Europe - Venture Tape
 Venture Tape Europe Corp.
 Units 5 - 6, Faraday Close,
 Drayton Fields, Daventry,
 Northamptonshire, England NN11 8RD
 (0) 1327 876555
 FAX (0) 1327 876444

Australasia
 Venture Tape Australasia, Pty., Ltd.
 11B Production Drive
 Campbellfield, VIC 3061
 Australia
 (03) 9357 6025
 FAX (03) 9357 6045