

DOUBLE COATED POLYESTER FILM TAPE

Double coated polyester (PET) film tape

Features & Benefits

- High performance differential adhesive mounting tape product bonds to a wide variety of ether and ester foams, metals, glass, plastics and composites
- Removes cleanly without leaving residue
- Ideal for signs, nameplates and other nonper

Name	Imperial Typical Value	Typical Value (Metric)
Thickness Adhesive Exposed	1.5 mils	38.1 $\hat{1}$ / ₄ m
Thickness Adhesive Liner	1.5 mils	38.1 microns
Thickness Liner	4.6 mils	116.8 $\hat{1}$ / ₄ m
Peel Adhesion Exposed	70 oz/inch width	19.5 N/25 mm
Peel Adhesion Liner	20 oz/inch width	5.6 N/25 mm
Shear Strength Exposed	>168 hrs	>168 hrs
Shear Strength Liner	>168 hrs	>168 hrs
Minimum Appl	0 degrees F	-18 degrees C
Maximum Use Temp	250 degrees F	121 degrees C

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Contact Venture Tape today for a complete list of products or a free sample
 Toll Free North America 800-343-1076
 From United Kingdom 0-800-962-957
 From Australia 1-800-122-797
www.venturetape.com
www.boma.it



USA
 Venture Tape Corp.
 30 Commerce Road
 Rockland, MA 02370
 781-331-5900
 FAX 781-871-0065
www.venturetape.com

Europe - Venture Tape
 Venture Tape Europe Corp.
 Units 5 - 6, Faraday Close,
 Drayton Fields, Daventry,
 Northamptonshire, England NN11 8RD
 (0) 1327 876555
 FAX (0) 1327 876444

Australasia
 Venture Tape Australasia, Pty., Ltd.
 11B Production Drive
 Campbellfield, VIC 3061
 Australia
 (03) 9357 6025
 FAX (03) 9357 6045