

## HIGH PERFORMANCE 3 MIL TRANSFER TAPE

A 3 mil (75 micron) transfer tape with an extremely aggressive, high tack acrylic adhesive system. This tape exhibits very good chemical and solvent resistance. Adhesion is excellent to low energy surfaces, metals, glass, foils, paper, and most engineering plastics.

Name	Imperial Typical Value	Typical Value (Metric)
Peel Adhesion Exposed	76 oz/inch width	21.5 N/2.5 cm
Shear Strength Exposed	6 hrs @ 2.2 psi	6 hrs @ 15.2 kPa
Minimum Appl	20 degrees F	-6.7 degrees C
Maximum Use Temp	200 degrees F	93 degrees C

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Contact Venture Tape today for a complete list of products or a free sample  
 Toll Free North America 800-343-1076  
 From United Kingdom 0-800-962-957  
 From Australia 1-800-122-797  
[www.venturetape.com](http://www.venturetape.com)  
[www.boma.it](http://www.boma.it)



**USA**  
 Venture Tape Corp.  
 30 Commerce Road  
 Rockland, MA 02370  
 781-331-5900  
 FAX 781-871-0065  
[www.venturetape.com](http://www.venturetape.com)

**Europe - Venture Tape**  
 Venture Tape Europe Corp.  
 Units 5 - 6, Faraday Close,  
 Drayton Fields, Daventry,  
 Northamptonshire, England NN11 8RD  
 (0) 1327 876555  
 FAX (0) 1327 876444

**Australasia**  
 Venture Tape Australasia, Pty., Ltd.  
 11B Production Drive  
 Campbellfield, VIC 3061  
 Australia  
 (03) 9357 6025  
 FAX (03) 9357 6045