

1MIL POLYESTER FILM COATED TAPE

A 1mil polyester film coated with a differential synthetic pressure sensitive adhesive system. The exposed side is a high tack and high shear adhesive system with excellent adhesion to most metals and plastics. The liner side is an extremely aggressive, high tack adhesive system that provides exceptional peel and shear properties. This adhesive system has excellent adhesion to low surface energy materials.

Name	Imperial Typical Value	Typical Value (Metric)
Thickness Adhesive Exposed	2.3-2.7 mils	0.0584-0.0686 mm
Peel Adhesion Exposed	48 oz/inch width	13.6 N/2.5 cm
Peel Adhesion Liner	64 oz/inch width	18.1 N/2.5 cm
Shear Strength Exposed	100 hrs @ 2.2 psi	100 hrs @ 15.2 kPa
Tensile Strength	12.5 lbs/inch width	56.48 N/2.5 cm
Elongation	80%	80%
Minimum Appl	40 degrees F	4.4 degrees C
Maximum Use Temp	250 degrees F	121 degrees C

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Contact Venture Tape today for a complete list of products or a free sample
 Toll Free North America 800-343-1076
 From United Kingdom 0-800-962-957
 From Australia 1-800-122-797
www.venturetape.com
www.boma.it



USA
 Venture Tape Corp.
 30 Commerce Road
 Rockland, MA 02370
 781-331-5900
 FAX 781-871-0065
www.venturetape.com

Europe - Venture Tape
 Venture Tape Europe Corp.
 Units 5 - 6, Faraday Close,
 Drayton Fields, Daventry,
 Northamptonshire, England NN11 8RD
 (0) 1327 876555
 FAX (0) 1327 876444

Australasia
 Venture Tape Australasia, Pty., Ltd.
 11B Production Drive
 Campbellfield, VIC 3061
 Australia
 (03) 9357 6025
 FAX (03) 9357 6045