

560

DOUBLE COATED WHITE VINYL FILM

A 3.4 mil (86 micron), white vinyl film carrier with an aggressive synthetic rubber based adhesive system with high peel strength. Especially good adhesion to fabrics and leather

Name	Imperial Typical Value	Typical Value (Metric)
Thickness Carrier	3.4 mils	0.086 mm
Thickness Adhesive Exposed	2.5 mils	0.064 mm
Peel Adhesion Exposed	50 oz/inch width	14.25 N/2.5 cm
Shear Strength Exposed	1 psi	6.9 kPa
Tensile Strength	18 lbs/inch width	81.5 N/2.5 cm
Elongation	150%	150%
Minimum Appl	40 degrees F	4 degrees C
Maximum Use Temp	175 degrees F	80 degrees C

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Contact Venture Tape today for a complete list of products or a free sample
Toll Free North America 800-343-1076
From United Kingdom 0-800-962-957
From Australia 1-800-122-797
www.venturetape.com
www.boma.it



VentureTape®

USA
Venture Tape Corp.
30 Commerce Road
Rockland, MA 02370
781-331-5900
FAX 781-871-0065
www.venturetape.com

Europe - Venture Tape
Venture Tape Europe Corp.
Units 5 - 6, Faraday Close,
Drayton Fields, Daventry,
Northamptonshire, England NN11 8RD
(0) 1327 876555
FAX (0) 1327 876444

Australasia
Venture Tape Australasia, Pty., Ltd.
11B Production Drive
Campbellfield, VIC 3061
Australia
(03) 9357 6025
FAX (03) 9357 6045