

0.5 MIL PERMANENT/REMOVABLE DOUBLE COATED PET

A 0.5 mil (12 micron) permanent/removable double coated polyester film tape where the exposed side is a high peel, high shear acrylic adhesive. This adhesive bonds well to most urethane, polyethylene, EPDM, nitrile PVC, and most standard gasket materials. The liner side is a high tack removable acrylic. Both adhesives are highly resistant to UV, moisture, and weathering.

Name	Imperial Typical Value	Typical Value (Metric)
Thickness Carrier	0.5 mils	0.0127 mm
Thickness Adhesive Exposed	2.75 mils	0.0699 mm
Peel Adhesion Exposed	79.0 oz/inch width	22.4 N/2.5 cm
Peel Adhesion Liner	27.0 oz/inch width	7.6 N/2.5 cm
Shear Strength Exposed	Indefinite @ 2.2 psi	Indefinite @ 15.2 kPa
Tensile Strength	7.5 lbs/inch width	33.9 N/2.5 cm
Elongation	100%	100%
Minimum Appl	30 degrees F	-1 degrees C
Maximum Use Temp	250 degrees F	121 degrees C

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Contact Venture Tape today for a complete list of products or a free sample
 Toll Free North America 800-343-1076
 From United Kingdom 0-800-962-957
 From Australia 1-800-122-797
www.venturetape.com
www.boma.it



USA
 Venture Tape Corp.
 30 Commerce Road
 Rockland, MA 02370
 781-331-5900
 FAX 781-871-0065
www.venturetape.com

Europe - Venture Tape
 Venture Tape Europe Corp.
 Units 5 - 6, Faraday Close,
 Drayton Fields, Daventry,
 Northamptonshire, England NN11 8RD
 (0) 1327 876555
 FAX (0) 1327 876444

Australasia
 Venture Tape Australasia, Pty., Ltd.
 11B Production Drive
 Campbellfield, VIC 3061
 Australia
 (03) 9357 6025
 FAX (03) 9357 6045