

CREPE PAPER DC TAPE

A conformable, impregnated, crepe paper coated on both sides with an extremely aggressive, high tack synthetic rubber based adhesive system. This adhesive system has excellent balance of peel and shear properties along with good heat resistance.

Name	Imperial Typical Value	Typical Value (Metric)
Market B Product	Golf Club Grip Tape	
Market B Descr	Venture Tape 571 is a 4-mil (102 $\frac{1}{4}$ m) double s	Venture Tape 571 applies easily and excels in demolding temp
Thickness Carrier	4.0 mils	0.1016 mm
Thickness Adhesive Exposed	3.0 mils	0.0762 mm
Peel Adhesion Exposed	96 oz/inch width	27.1 N/2.5 cm
Shear Strength Exposed	Indefinite @ 2.2 psi	Indefinite @ 15.2 kPa
Tensile Strength	20 lbs/inch width	90.4 N/2.5 cm
Elongation	9%	9%
Minimum Appl	40 degrees F	4 degrees C
Maximum Use Temp	175 degrees F	80 degrees C

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Contact Venture Tape today for a complete list of products or a free sample
 Toll Free North America 800-343-1076
 From United Kingdom 0-800-962-957
 From Australia 1-800-122-797
www.venturetape.com
www.boma.it



USA
 Venture Tape Corp.
 30 Commerce Road
 Rockland, MA 02370
 781-331-5900
 FAX 781-871-0065
www.venturetape.com

Europe - Venture Tape
 Venture Tape Europe Corp.
 Units 5 - 6, Faraday Close,
 Drayton Fields, Daventry,
 Northamptonshire, England NN11 8RD
 (0) 1327 876555
 FAX (0) 1327 876444

Australasia
 Venture Tape Australasia, Pty., Ltd.
 11B Production Drive
 Campbellfield, VIC 3061
 Australia
 (03) 9357 6025
 FAX (03) 9357 6045