

0.5 MIL DOUBLE COATED POLYESTER FILM TAPE

A 0.5 mil (12 micron) double coated polyester film tape where the exposed side offers excellent adhesion to low energy surfaces, metals, glass, foils, papers, and most engineering plastics. The liner side adheres to plastics, metals, and wood. This product has very good dielectric properties.

Name	Imperial Typical Value	Typical Value (Metric)
Thickness Carrier	0.5 mils	0.0127 mm
Thickness Adhesive Exposed	3.25 mils	0.0826 mm
Peel Adhesion Exposed	70.0 oz/inch width	19.8 N/2.5 cm
Peel Adhesion Liner	65.0 oz/inch width	18.4 N/2.5 cm
Shear Strength Exposed	12+ hrs @ 1.1 psi	12+ hrs @ 7.6 kPa
Tensile Strength	7.5 lbs/inch width	33.9 N/2.5 cm
Elongation	100%	100%
Minimum Appl	20 degrees F	-7 degrees C
Maximum Use Temp	175 degrees F	80 degrees C

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Contact Venture Tape today for a complete list of products or a free sample
 Toll Free North America 800-343-1076
 From United Kingdom 0-800-962-957
 From Australia 1-800-122-797
www.venturetape.com
www.boma.it



USA
 Venture Tape Corp.
 30 Commerce Road
 Rockland, MA 02370
 781-331-5900
 FAX 781-871-0065
www.venturetape.com

Europe - Venture Tape
 Venture Tape Europe Corp.
 Units 5 - 6, Faraday Close,
 Drayton Fields, Daventry,
 Northamptonshire, England NN11 8RD
 (0) 1327 876555
 FAX (0) 1327 876444

Australasia
 Venture Tape Australasia, Pty., Ltd.
 11B Production Drive
 Campbellfield, VIC 3061
 Australia
 (03) 9357 6025
 FAX (03) 9357 6045