

584

0.5 MIL DC PET

Venture Tape 584 is a double coated polyester film tape coated on both sides with a thick coating of an aggressive, high heat resistant acrylic pressure sensitive adhesive (PSA). A high performance splicing tape specifically designed for demanding splicing applications in continuous web processes, Venture Tape 584 is especially suitable for corrugated paper applications.

Features & Benefits

- High heat, high performance splicing tape product meets the most demanding application requirements
- Excellent peel, tack and shear
- Adheres well to Kraft and waxy coated papers
- Humidity and environmental condition resistance
- Excellent p

Name	Imperial Typical Value	Typical Value (Metric)
Thickness Carrier	0.5 mils	
Thickness Adhesive Exposed	2.0 mils	
Thickness Adhesive Liner	2.0 mils	
Thickness Liner	3.2 mils	
Peel Adhesion Exposed	50 oz/inch width	
Shear Strength Exposed	>168 hrs	
Tensile Strength	8 lbs/inch width	
Elongation	100%	
Minimum Appl	40 degrees F	4 degrees C
Maximum Use Temp	400 degrees F	205 degrees C

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Contact Venture Tape today for a complete list of products or a free sample
Toll Free North America 800-343-1076
From United Kingdom 0-800-962-957
From Australia 1-800-122-797
www.venturetape.com
www.boma.it



USA
Venture Tape Corp.
30 Commerce Road
Rockland, MA 02370
781-331-5900
FAX 781-871-0065
www.venturetape.com

Europe - Venture Tape
Venture Tape Europe Corp.
Units 5 - 6, Faraday Close,
Drayton Fields, Daventry,
Northamptonshire, England NN11 8RD
(0) 1327 876555
FAX (0) 1327 876444

Australasia
Venture Tape Australasia, Pty., Ltd.
11B Production Drive
Campbellfield, VIC 3061
Australia
(03) 9357 6025
FAX (03) 9357 6045