

HIGH SHEAR DOUBLE COATED POLYESTER TAPE

A 1/2 mil (12 micron) polyester film coated on both sides with 1.5 mils (38 microns) of a high shear acrylic adhesive system. This adhesive system allows for superior bonding and conformability to irregular as well as flat surfaces, and bonds well to most substrates including most low surface energy plastics.

Name	Imperial Typical Value	Typical Value (Metric)
Peel Adhesion Exposed	75.0 oz/inch width	21.2 N/2.5 cm
Shear Strength Exposed	Indefinite @ 4.4 psi	Indefinite @ 30.4 kPa
Tensile Strength	7.5 lbs/inch width	33.9 N/2.5cm
Elongation	100%	100%
Minimum Appl	10 degrees F	-12 degrees C
Maximum Use Temp	425 degrees F	219 degrees C

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Contact Venture Tape today for a complete list of products or a free sample
 Toll Free North America 800-343-1076
 From United Kingdom 0-800-962-957
 From Australia 1-800-122-797
www.venturetape.com
www.boma.it



USA
 Venture Tape Corp.
 30 Commerce Road
 Rockland, MA 02370
 781-331-5900
 FAX 781-871-0065
www.venturetape.com

Europe - Venture Tape
 Venture Tape Europe Corp.
 Units 5 - 6, Faraday Close,
 Drayton Fields, Daventry,
 Northamptonshire, England NN11 8RD
 (0) 1327 876555
 FAX (0) 1327 876444

Australasia
 Venture Tape Australasia, Pty., Ltd.
 11B Production Drive
 Campbellfield, VIC 3061
 Australia
 (03) 9357 6025
 FAX (03) 9357 6045