

DOUBLE COATED HIGH SHEAR POLYESTER TAPE

A double coated 0.5 mil (.0050), polyester film coated on both sides with an extremely high shear, aggressive, high performance acrylic adhesive. The adhesive has excellent resistance to solvents, UV, humidity, and high and low temperatures. Good affinity to low surface energy plastics.

Name	Imperial Typical Value	Typical Value (Metric)
Peel Adhesion Exposed	56 oz/inch width	15.8 N/2.5 cm
Shear Strength Exposed	4 psi	27.6 kPa
Tensile Strength	7.5 lbs/inch width	33.9 N/2.5 cm
Elongation	100%	100%
Minimum Appl	-34 degrees F	-37 degrees C
Maximum Use Temp	275 degrees F	135 degrees C

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Contact Venture Tape today for a complete list of products or a free sample
 Toll Free North America 800-343-1076
 From United Kingdom 0-800-962-957
 From Australia 1-800-122-797
www.venturetape.com
www.boma.it



USA
 Venture Tape Corp.
 30 Commerce Road
 Rockland, MA 02370
 781-331-5900
 FAX 781-871-0065
www.venturetape.com

Europe - Venture Tape
 Venture Tape Europe Corp.
 Units 5 - 6, Faraday Close,
 Drayton Fields, Daventry,
 Northamptonshire, England NN11 8RD
 (0) 1327 876555
 FAX (0) 1327 876444

Australasia
 Venture Tape Australasia, Pty., Ltd.
 11B Production Drive
 Campbellfield, VIC 3061
 Australia
 (03) 9357 6025
 FAX (03) 9357 6045