

## MIRROR MOUNTING TAPE

Venture Tape 632 is a 31.25 mil (0.8mm) double coated polyethylene foam tape designed for mirror mounting, sealing, gasketing, and sound and vibration damping applications. The highly conformable foam, coupled with a high performance rubber adhesive, creates a reliable bond on a wide variety of high and low energy surfaces, providing optimum performance and durability.

Name	Imperial Typical Value	Typical Value (Metric)
Thickness Carrier	31.3 mils	0.8 mm
Thickness Adhesive Exposed	2.3 mils	57.2 Åµm
Thickness Adhesive Liner	2.3 mils	57.2 Åµm
Thickness Liner	4.7 mils	119.4 Åµm
Peel Adhesion Exposed	100 oz/inch width	27.8 N/25 mm
Peel Adhesion Liner	100 oz/inch width	27.8 N/25 mm
Shear Strength Exposed	>76 hrs	>76 hrs
Shear Strength Liner	>76 hrs	>76 hrs
Tensile Strength	6.0 lbs/inch width	27 N/25 mm width
Elongation	300%	300%
Minimum Appl	50 degrees F	10 degrees C
Maximum Use Temp	175 degrees F	degrees C

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

**Contact Venture Tape today for a complete list of products or a free sample**  
Toll Free North America 800-343-1076  
From United Kingdom 0-800-962-957  
From Australia 1-800-122-797  
[www.venturetape.com](http://www.venturetape.com)  
[www.boma.it](http://www.boma.it)



**USA**  
Venture Tape Corp.  
30 Commerce Road  
Rockland, MA 02370  
781-331-5900  
FAX 781-871-0065  
[www.venturetape.com](http://www.venturetape.com)

**Europe - Venture Tape**  
Venture Tape Europe Corp.  
Units 5 - 6, Faraday Close,  
Drayton Fields, Daventry,  
Northamptonshire, England NN11 8RD  
(O) 1327 876555  
FAX (O) 1327 876444

**Australasia**  
Venture Tape Australasia, Pty., Ltd.  
11B Production Drive  
Campbellfield, VIC 3061  
Australia  
(O3) 9357 6025  
FAX (O3) 9357 6045