

716

MIRROR MOUNTING TAPE

Venture Tape 716 is a 62.5 mil (1.6mm) double coated polyethylene foam tape designed for mirror mounting, sealing, gasketing, and sound and vibration damping applications. The highly conformable foam, coupled with a high performance acrylic adhesive, creates a reliable bond on a wide variety of high and low energy surfaces, providing optimum performance and durability.

Features & Benefits

- Excellent performance on a wide variety of

Name	Imperial Typical Value	Typical Value (Metric)
Thickness Carrier	62.5 mils	1.6 mm
Thickness Adhesive Exposed	2.3 mils	57.2 μm
Thickness Adhesive Liner	2.3 mils	57.2 μm
Thickness Liner	4.7 mils	119.4 μm
Peel Adhesion Exposed	90 oz/inch width	25.0 N/25 mm
Peel Adhesion Liner	90 oz/inch width	25.0 N/25 mm
Shear Strength Exposed	>100 hrs	>100 hrs
Shear Strength Liner	>100 hrs	>100 hrs
Tensile Strength	6.0 lbs/inch width	27 N/25 mm width
Elongation	3000%	300%
Minimum Appl	30 degrees F	-1 degrees C
Maximum Use Temp	200 degrees F	93 degrees C

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Contact Venture Tape today for a complete list of products or a free sample
Toll Free North America 800-343-1076
From United Kingdom 0-800-962-957
From Australia 1-800-122-797
www.venturetape.com
www.boma.it



VentureTape[®]

USA
Venture Tape Corp.
30 Commerce Road
Rockland, MA 02370
781-331-5900
FAX 781-871-0065
www.venturetape.com

Europe - Venture Tape
Venture Tape Europe Corp.
Units 5 - 6, Faraday Close,
Drayton Fields, Daventry,
Northamptonshire, England NN11 8RD
(0) 1327 876555
FAX (0) 1327 876444

Australasia
Venture Tape Australasia, Pty., Ltd.
11B Production Drive
Campbellfield, VIC 3061
Australia
(03) 9357 6025
FAX (03) 9357 6045