

HIGH TACK 2 MIL (50 MICRON) ACRYLIC

An aggressive, 2 mil (50 micron) clear acrylic, unsupported transfer adhesive with excellent resistance to oxidation, UV and heat. This product has high tack and shear as well as good adhesion to metals, low surface energy plastics, most elastomers and untreated olefins.

Name	Imperial Typical Value	Typical Value (Metric)
Thickness Adhesive Exposed	2.0 mils	0.051 mm
Peel Adhesion Exposed	35 oz/inch width	9.8 N/2.5 cm
Shear Strength Exposed	15 hrs @ 2.2 psi	15 hrs @ 15.2 kPa
Minimum Appl	30 degrees F	-1 degrees C
Maximum Use Temp	275 degrees F	135 degrees C

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Contact Venture Tape today for a complete list of products or a free sample
 Toll Free North America 800-343-1076
 From United Kingdom 0-800-962-957
 From Australia 1-800-122-797
www.venturetape.com
www.boma.it



USA
 Venture Tape Corp.
 30 Commerce Road
 Rockland, MA 02370
 781-331-5900
 FAX 781-871-0065
www.venturetape.com

Europe - Venture Tape
 Venture Tape Europe Corp.
 Units 5 - 6, Faraday Close,
 Drayton Fields, Daventry,
 Northamptonshire, England NN11 8RD
 (0) 1327 876555
 FAX (0) 1327 876444

Australasia
 Venture Tape Australasia, Pty., Ltd.
 11B Production Drive
 Campbellfield, VIC 3061
 Australia
 (03) 9357 6025
 FAX (03) 9357 6045