

794

HIGH TRACK 4 MIL (100 MICRON) ACRYLIC TRANSFER ADHESIVE

An extremely aggressive, 4 mil (100 micron) clear acrylic, unsupported adhesive formulation. Excellent resistance to oxidation, UV and heat. High tack and shear. Good adhesion to metals. low surface energy plastics, most elastomers and untreated olefins.

Name	Imperial Typical Value	Typical Value (Metric)
Peel Adhesion Exposed	120 oz/inch width	33.9 N/2.5 cm
Shear Strength Exposed	Indefinite @ 2 psi	Indefinite @ 13.8 kPa
Minimum Appl	-32 degrees F	-38 degrees C
Maximum Use Temp	275 degrees F	135 degrees C

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Contact Venture Tape today for a complete list of products or a free sample
Toll Free North America 800-343-1076
From United Kingdom 0-800-962-957
From Australia 1-800-122-797
www.venturetape.com
www.boma.it



VentureTape®

USA
Venture Tape Corp.
30 Commerce Road
Rockland, MA 02370
781-331-5900
FAX 781-871-0065
www.venturetape.com

Europe - Venture Tape
Venture Tape Europe Corp.
Units 5 - 6, Faraday Close,
Drayton Fields, Daventry,
Northamptonshire, England NN11 8RD
(0) 1327 876555
FAX (0) 1327 876444

Australasia
Venture Tape Australasia, Pty., Ltd.
11B Production Drive
Campbellfield, VIC 3061
Australia
(03) 9357 6025
FAX (03) 9357 6045