

## 2.5 MIL (62.5 MICRON) TRANSPARENT POLYETHYLENE

A 2.5 mil (62.5 micron) strong and conformable transparent polyethylene film tape with a very high tack, UV resistant acrylic adhesive. This product has excellent peel adhesion and cold stick as well as excellent resistance to moisture, acids, chemicals, oils, abrasion, and weathering.

Name	Imperial Typical Value	Typical Value (Metric)
Thickness Carrier	1.5 mils	
Thickness Adhesive Exposed	2.5 mils	
Peel Adhesion Exposed	60 oz/inch width	17 N/2.5 cm
Shear Strength Exposed	Indefinite @ 2.2 psi	Indefinite @ 15.2 kPa
Tensile Strength	8 lbs/inch width	36.1 N/2.5 cm
Minimum Appl	10 degrees F	-12 degrees C
Maximum Use Temp	250 degrees F	120 degrees C

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Contact Venture Tape today for a complete list of products or a free sample  
 Toll Free North America 800-343-1076  
 From United Kingdom 0-800-962-957  
 From Australia 1-800-122-797  
[www.venturetape.com](http://www.venturetape.com)  
[www.boma.it](http://www.boma.it)



**USA**  
 Venture Tape Corp.  
 30 Commerce Road  
 Rockland, MA 02370  
 781-331-5900  
 FAX 781-871-0065  
[www.venturetape.com](http://www.venturetape.com)

**Europe - Venture Tape**  
 Venture Tape Europe Corp.  
 Units 5 - 6, Faraday Close,  
 Drayton Fields, Daventry,  
 Northamptonshire, England NN11 8RD  
 (0) 1327 876555  
 FAX (0) 1327 876444

**Australasia**  
 Venture Tape Australasia, Pty., Ltd.  
 11B Production Drive  
 Campbellfield, VIC 3061  
 Australia  
 (03) 9357 6025  
 FAX (03) 9357 6045