

912

BLACK POLYETHYLENE TAPE

Venture Tape 912 is a black polyethylene surface protection tape coated with a specially formulated removable acrylic pressure sensitive adhesive (PSA). Specifically designed as a protection and masking tape, Venture Tape 912 may also be used as a weather seal for applying plastic storm windows, film can sealing, ink container sealing, and polyethylene sheeting where removability is desired.

Name	Imperial Typical Value	Typical Value (Metric)
Thickness Carrier	4.8 mils	
Thickness Adhesive Exposed	1.0 mils	
Peel Adhesion Exposed	24 oz/inch width	
Shear Strength Exposed	>168 hrs	
Tensile Strength	13 lbs/inch width	
Elongation	250%	
Minimum Appl	30 degrees F	-1 degrees C
Maximum Use Temp	175 degrees F	80 degrees C

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Contact Venture Tape today for a complete list of products or a free sample
Toll Free North America 800-343-1076
From United Kingdom 0-800-962-957
From Australia 1-800-122-797
www.venturetape.com
www.boma.it



VentureTape[®]

USA
Venture Tape Corp.
30 Commerce Road
Rockland, MA 02370
781-331-5900
FAX 781-871-0065
www.venturetape.com

Europe - Venture Tape
Venture Tape Europe Corp.
Units 5 - 6, Faraday Close,
Drayton Fields, Daventry,
Northamptonshire, England NN11 8RD
(0) 1327 876555
FAX (0) 1327 876444

Australasia
Venture Tape Australasia, Pty., Ltd.
11B Production Drive
Campbellfield, VIC 3061
Australia
(03) 9357 6025
FAX (03) 9357 6045