

# 918

## SHRINK FILM SPLICING TAPE

A 8 mil (200 micron) thick white UV stable polyethylene film coated with a high quick stick, synthetic rubber based adhesive system. The adhesive has excellent shear strength and good high temperature resistance with clean removability from fiberglass, stainless steel and aluminum after long term outdoor exposure.

Name	Imperial Typical Value	Typical Value (Metric)
Peel Adhesion Exposed	27 oz/inch width	7.6 N/2.5 cm
Shear Strength Exposed	24+ hrs @ 10 psi	24+ hrs @ 69 kPa
Tensile Strength	22 lbs/inch width	99.4 N/2.5 cm
Elongation	400%	400%
Minimum Appl	40 degrees F	4 degrees C
Maximum Use Temp	175 degrees F	80 degrees C

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Contact Venture Tape today for a complete list of products or a free sample  
Toll Free North America 800-343-1076  
From United Kingdom 0-800-962-957  
From Australia 1-800-122-797  
[www.venturetape.com](http://www.venturetape.com)  
[www.boma.it](http://www.boma.it)



**USA**  
Venture Tape Corp.  
30 Commerce Road  
Rockland, MA 02370  
781-331-5900  
FAX 781-871-0065  
[www.venturetape.com](http://www.venturetape.com)

**Europe - Venture Tape**  
Venture Tape Europe Corp.  
Units 5 - 6, Faraday Close,  
Drayton Fields, Daventry,  
Northamptonshire, England NN11 8RD  
(0) 1327 876555  
FAX (0) 1327 876444

**Australasia**  
Venture Tape Australasia, Pty., Ltd.  
11B Production Drive  
Campbellfield, VIC 3061  
Australia  
(03) 9357 6025  
FAX (03) 9357 6045