

1581A

UL181A P FOIL TAPE

Venture Tape 1581A is a 2.0 mil (50μm) high temperature, high tensile strength aluminum foil coated with an extremely aggressive all weather solvent acrylic pressure sensitive adhesive. Conformable foil applies easily to both fibrous and sheet metal ducts on flat and irregular surfaces. Venture Tape 1581A excels in demanding temperature and humidity applications and provides superior performance and durability over a wide range of environmental conditions.

Name	Imperial Typical Value	Typical Value (Metric)
Thickness Carrier	2.0 mils	100 μ
Thickness Adhesive Exposed	2.0 mils	100 μ
Peel Adhesion Exposed	85 oz/inch	24.2 N/2.5 cm
Tensile Strength	25 lbs/inch width	113.2 N/2.5 cm
Elongation	4.3%	4.3%
Minimum Appl	20 degrees F	-7 degrees C
Maximum Use Temp	350 degrees F	177 degrees C

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Contact Venture Tape today for a complete list of products or a free sample
Toll Free North America 800-343-1076
From United Kingdom 0-800-962-957
From Australia 1-800-122-797
www.venturetape.com
www.boma.it



USA
Venture Tape Corp.
30 Commerce Road
Rockland, MA 02370
781-331-5900
FAX 781-871-0065
www.venturetape.com

Europe - Venture Tape
Venture Tape Europe Corp.
Units 5 - 6, Faraday Close,
Drayton Fields, Daventry,
Northamptonshire, England NN11 8RD
(0) 1327 876555
FAX (0) 1327 876444

Australasia
Venture Tape Australasia, Pty., Ltd.
11B Production Drive
Campbellfield, VIC 3061
Australia
(03) 9357 6025
FAX (03) 9357 6045