

# 300

## PVC TAPE

*A thin, strong, low stretch, self wound PVC tape coated with an aggressive acrylic adhesive system. This tape is highly conformable and has high temperature performance. This product has clean removability after bake cycle. This product has a smooth unwind and is made to handle compound curves and detail work.*

Name	Imperial Typical Value	Typical Value (Metric)
Peel Adhesion Exposed	23 oz/inch width	6.3 N/2.5 cm
Tensile Strength	15 lbs/inch width	67.8 N/2.5 cm
Elongation	190%	190%
Minimum Appl	40 degrees F	4 degrees C
Maximum Use Temp	325 degrees F	162 degrees C

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

**Contact Venture Tape today for a complete list of products or a free sample**  
Toll Free North America 800-343-1076  
From United Kingdom 0-800-962-957  
From Australia 1-800-122-797  
[www.venturetape.com](http://www.venturetape.com)  
[www.boma.it](http://www.boma.it)



**USA**  
Venture Tape Corp.  
30 Commerce Road  
Rockland, MA 02370  
781-331-5900  
FAX 781-871-0065  
[www.venturetape.com](http://www.venturetape.com)

**Europe - Venture Tape**  
Venture Tape Europe Corp.  
Units 5 - 6, Faraday Close,  
Drayton Fields, Daventry,  
Northamptonshire, England NN11 8RD  
(0) 1327 876555  
FAX (0) 1327 876444

**Australasia**  
Venture Tape Australasia, Pty., Ltd.  
11B Production Drive  
Campbellfield, VIC 3061  
Australia  
(03) 9357 6025  
FAX (03) 9357 6045