

## HIGH PERFORMANCE PAPER TAPE

An extremely aggressive high performance rubber based adhesive system coated on a heavy weight moisture stable natural craft paper. The heavy aggressive adhesive thickness allows this tape to bond well to a wide variety of materials.

Name	Imperial Typical Value	Typical Value (Metric)
Thickness Carrier	5 mils	0.1270 mm
Thickness Adhesive Exposed	3 mils	0.0762 mm
Peel Adhesion Exposed	120 oz/inch width	34N/2.5 cm
Shear Strength Exposed	Indefinite @ 2.2 psi	Indefinite @ 15.2 kPa
Tensile Strength	38 lbs/inch width	172 N/2.5 cm
Elongation	35%	35%
Standard Widths	1" to 60	" 25.4 to 1524 mm
Standard Length	60 to 274 yds	54.7 to 250 m

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Contact Venture Tape today for a complete list of products or a free sample  
 Toll Free North America 800-343-1076  
 From United Kingdom 0-800-962-957  
 From Australia 1-800-122-797  
[www.venturetape.com](http://www.venturetape.com)  
[www.boma.it](http://www.boma.it)



**USA**  
 Venture Tape Corp.  
 30 Commerce Road  
 Rockland, MA 02370  
 781-331-5900  
 FAX 781-871-0065  
[www.venturetape.com](http://www.venturetape.com)

**Europe - Venture Tape**  
 Venture Tape Europe Corp.  
 Units 5 - 6, Faraday Close,  
 Drayton Fields, Daventry,  
 Northamptonshire, England NN11 8RD  
 (0) 1327 876555  
 FAX (0) 1327 876444

**Australasia**  
 Venture Tape Australasia, Pty., Ltd.  
 11B Production Drive  
 Campbellfield, VIC 3061  
 Australia  
 (03) 9357 6025  
 FAX (03) 9357 6045