

440

TYVEK INDUSTRIAL TAPE

A tough spun bonded polyolefin (Tyvek) substrate coated with an aggressive, cold weather, acrylic adhesive system.

Name	Imperial Typical Value	Typical Value (Metric)
Thickness Carrier	5.4 mils	0.1371 mm
Thickness Adhesive Exposed	1.6 mils	0.0406 mm
Peel Adhesion Exposed	45 oz/inch width	12.7 N/2.5 cm
Shear Strength Exposed	24+ hrs @ 2.2 psi	24 + hrs @ 15.2 kPa
Tensile Strength	20 lbs/inch width	90.3 N/2.5 cm
Elongation	12%	12%
Minimum Appl	-25 degrees F	-32 degrees C
Maximum Use Temp	200 degrees F	93 degreesC

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Contact Venture Tape today for a complete list of products or a free sample
Toll Free North America 800-343-1076
From United Kingdom 0-800-962-957
From Australia 1-800-122-797
www.venturetape.com
www.boma.it



VentureTape®

USA
Venture Tape Corp.
30 Commerce Road
Rockland, MA 02370
781-331-5900
FAX 781-871-0065
www.venturetape.com

Europe - Venture Tape
Venture Tape Europe Corp.
Units 5 - 6, Faraday Close,
Drayton Fields, Daventry,
Northamptonshire, England NN11 8RD
(0) 1327 876555
FAX (0) 1327 876444

Australasia
Venture Tape Australasia, Pty., Ltd.
11B Production Drive
Campbellfield, VIC 3061
Australia
(03) 9357 6025
FAX (03) 9357 6045